## **Zefon®** Aluminum Cyclone for Respirable Dust

The Zefon® Respirable Dust Aluminum Cyclone is used in conjunction with 25mm or 37mm 3 piece filter cassettes to separate and remove larger particles from the respirable particles collected on the cassette's filter. This Zefon® cyclone is a replica of the SKC Aluminum Cyclone\*. The inner workings have been precisely machined to exactly match that of the SKC Cyclone with only slight cosmetic changes to the exterior.

As a result, the collection efficiency curve meets the standards set forth by ACGIH/ ISO/CEN for a respirable curve with a median 50% cut point of 4 micron at 2.5 LPM flowrate.

A cyclone holder and 25mm or 37mm 3 piece filter cassette are required for use of the Zefon® Aluminum Cyclone. Both the Zefon® Cassette Cyclone holder (#ZA0061) and the SKC holder (#225-1) are compatible with the Zefon® Aluminum Cyclone.



ZA0060 ZA0075

#### Features:

- Aluminum construction is static
- Lightweight 30 grams
- Fully interchangeable with SKC Aluminum Cyclone
- conductive, eliminating interference Specified in NIOSH method 0600 for Respirable Particulates, and NIOSH 7500 for Silica, Crystalline

| PRODUCT | DESCRIPTION  |
|---------|--|
| ZA0060  | Zefon® 37mm Aluminum Cyclone for Respirable Dust                 |
| ZA0075  | Zefon® 25mm Aluminum Cyclone for Respirable Dust                 |
| ZA0062  | Zefon® 37mm Aluminum Cyclone for Respirable Dust with Holder     |
| ZA0076  | Zefon® 25mm Aluminum Cyclone for Respirable Dust with Holder     |
| ZA0061  | Zefon <sup>®</sup> Universal Cassette and/or Cyclone Holder only |
| ZA0066  | Replacement Grit Pots for Aluminum Cyclone, 25/pk                |
| ZA0067  | Replacement O-Rings for Aluminum Cyclone, 5/pk                   |



<sup>\*</sup>Performance tests indicate no statistical difference between the SKC Aluminum Cyclone and the  ${f Z} e fon^{@}$  Aluminum Cyclone.



## **Aluminum Cyclone Calibration Adapter**

A chamber specifically designed to fit over the Zefon® aluminum cyclone and connect 1/4" ID tubing for flow calibration. This provides the best calibration option by taking an actual measurement as close to the cyclone inlet as possible. Chamber fits both Zefon® brand and SKC brand 37mm and 25mm aluminum cyclones.

| PRODUCT | DESCRIPTION                                 |
|---------|---|
| ZA0011  | Zefon® Aluminum Cyclone Calibration Adapter |



ZA0063

# **Zefon®** Calibration Jar

The Zefon® Cyclone Calibration Jar is a container with all the proper fittings and connections to calibrate Personal Sampling Pumps with the Zefon<sup>®</sup>, SKC, or Dorr-Oliver Cyclones, and inhalable dust samplers.

#### Features:

- Compatible with both Zefon® and SKC Aluminum Cyclones
- Complete with all fittings and Tygon® tubing for connecting the sampling pump

| PRODUCT | DESCRIPTION   |
|---------|---|
| ZA0063  | Zefon® 1 Liter Cyclone Calibration Jar (Aluminum Cyclone & Zefon® Conductive Nylon Cyclone) |
| ZA0085  | Zefon® 2 Liter Cyclone Calibration Jar (Sensidyne & Zefon® Dorr-Oliver Cyclone)             |
|         | DISTRIBUTED BY.   |

