



**BUILT FOR YOUR
ENVIRONMENT**

LOWFLOW

**DISCOVER LOW TO HIGH FLOW ASBESTOS AIR TESTING
WITH THE AIRBOX LOWFLOW PUMP**

With an adjustable valve to allow testing from 10 litres down to 2 litres, our Lowflow pump offers asbestos air testing flexibility with quality output.

**BUILT IN MECHANICAL
FLOW RATE ADJUSTER
ALLOWS THE PUMP
TO RUN AS LOW AS
2 LITRES/MIN**

(see over for full features
and specification)



LOWFLOW



FEATURES & BENEFITS



Adjustable flow rate
2-5litres/min (low)
5-10litres/min (high)



Fully waterproof casing (to IP65)
Quick, easy cleaning for decontamination



Two units fit together
For easy carrying in one hand

Programmable running cycles for repeatable tests

Robust and hard wearing, made from ABS structural foam

Easy access battery compartment for quick on-site battery replacement



Easy to use control panel with highly visible OLED display

Easy to store hose (patented)

Removable telescopic mast (up to 2m)

Low ownership costs
Up to 30% cheaper over 2 years than most other pumps*

Supplied with a 2 year warranty

Fully adjustable flow rate
Covers 2 - 10 litres/min

SPECIFICATIONS

Dimensions: H38cm x W 24cm x D12cm
Weight: 4.7 kg

Battery Pack: (1x) 12 Volt Lead Acid

CE/CA MARKED: Fully EMC compliant
Manufactured in the UK

SPEAK TO US

E: sales@airboxsp.com
T: +44(0)1903 524 600
W: WWW.AIRBOXSP.COM

* Contact us for calculations

Airbox is part of the FermionX Group
Airbox Sampling Products, Technology Centre,
Easting Close, Worthing, West Sussex BN14 8HQ