

# WaveMon RF-8

## Personal EMF Monitor

-  **OVEREXPOSURE WARNING**  
Audible, visual and vibratory alarm
-  **EMF EXPOSIMETER**  
Datalogger, instant & average values
-  **ICNIRP, 2013/35/EU, FCC, SC6**  
Occupational/Shaped response
-  **ELECTRIC AND MAGNETIC FIELD**  
Isotropic, RMS



Compliance  
with ITU-T K.145



Optional  
features



# WaveMon Applications



Worker's safety



Telecommunications



Energy



Railway



Medical



Labs



Aeronautical



Industry



Defense



Optional accredited calibration

## Technical Specifications

Sensor type	Isotropic, RMS diode technology	
Response	Shaped (ICNIRP 1998, Directive 2013/35/EU, FCC and Safety Code 6)	
Interface	1 button on/off, status and low battery LED	
Indicators	6 LEDs + Audio + Vibration	
Alarm threshold	2 limits adjustable by user	
Connectivity	Waterproof USB (for downloading data and recharging)	
Falling detection	Yes	
Autonomy	> 1 month (at 8 h/day, 5 days/week)	
Data logger	> 1 000 000 events	
Positioning	GPS and Altimeter	
Logging Interval	1 second to 60 minutes (adjustable by user)	
Averaging Interval	1 second to 60 minutes (adjustable by user)	
Battery Type	2 x AA NiMH battery rechargeable by USB	
Protection	IP 54	
LF immunity (50 - 60 Hz)	> 30 kV/m	
Temperature range	-20 / +50 °C (-4 / +122 °F) - Charging: 0 / +40 °C (+32 / + 104 °F)	
Size	174 x 42.5 x 33 mm (6.8 x 1.7 x 1.3 ")	
Weight	190 g (6.7 oz.)	
	<b>E-field</b>	<b>H-field</b>
Dynamic range	1 - 300 %	2 - 300 %
Linearity	±0.5 dB (2% - 200%)	±1 dB (5% - 200%)
Isotropic deviation	±1 dB @ 1GHz	±1 dB @ 400 MHz



DISTRIBUTED BY:

**Sedulitas**

PEOPLE | PASSION | PRECISION

info@sedulitas.co.za +27 (0)82 551 4001  
www.sedulitas.co.za

### Frequency range and response

Versions	Response shaped to	E-field	H-field
<b>WaveMon RF-8 ICN</b>	ICNIRP	<b>300 kHz - 8 GHz</b> ±3.5 dB	25 MHz - 1 GHz ±1 dB (30 MHz - 700 MHz) +0 dB/-2.5 dB (700 MHz - 850 MHz) +0 dB/-5 dB (850 MHz - 1 GHz)
<b>WaveMon RF-8 EUD</b>	EU Directive 2013/35		
<b>WaveMon RF-8 FCC</b>	FCC	<b>3 MHz - 8 GHz</b> ±3.5 dB	3 MHz - 1 GHz ±1 dB (3 MHz - 400 MHz) ±2 dB (400 MHz - 850 MHz) +0 dB/-4 dB (850 MHz - 1 GHz)
<b>WaveMon RF-8 SC6</b>	Safety Code 6	<b>10 MHz - 8 GHz</b> ±3.5 dB	25 MHz - 1 GHz ±2 dB (30 MHz - 800 MHz) +0 dB/-5 dB (800 MHz - 1 GHz)

Product specifications and descriptions in this document subject to change without notice