


ELIPSE® INTEGRA HALF-FACE MASK +HESPA™ A2P3 GAS AND DUST (R) FILTERS









Applications - Universal gases, dust. mist and fumes



ECKER

Welding

Metal fumes and dust in confined space (gas welding)





Standards

EN 140:1998 Mask Body
EN 14387:2004+A1:2008 A2P3 R D
(reusable filter suited for organic
gases and dust).
CE 2797 - UKCA 0086
EN 166:2001 2C-1.2 - 1.B.K.N 3-B
(UV Filter with Good Colour Recognition,
Optical Class 1, Medium Energy Impact,
Anti-Fog, Anti-Scratch, Protection against
Droplets and Splashes of Liquids).

Shelf Life

5 years (mask & filters). See storage conditions on Instructions for Use. Filters are re-usable and changeable.

Weight

Mask + Filter: net (S/M) 375 g; (M/L) 384 g gross (S/M) 495 g; (M/L) 511 g Filter: net 106 g each; both net 212 g, gross 240 g

Efficiency

P3 >99,95% for 0,3 μ particulate At 5000 ppm: Cyclohexane (C₆H₁₂) > 35 minutes

Material

- Mask: Medical grade TPE Conforms to ISO 10993-10: 2010 for irritations. Mask body latex and silicone free, odour free. Valve Body in Nylon, Inhalation/Exhalation diaphragm in Silicone. Four-point adjustable elasticated head and neck strap with comfort pad in TPE.
- Gas filters: Activated carbon sealed into a ABS shell.
- Particulate filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated. Particulate filters are integrated with the carbon element.
- Goggle: Polycarbonate with flow coating overmolded into soft TPE, permanently attached to the mask body by stainless steel clips.

Production

United Kingdom 100% of filters NaCl tested

	Code	Description	Quantity
	SPR673 (S/M) SPR674 (M/L)	A2P3 Elipse Integra complete with A2P3 filters	5 pcs. per box
	SPR670	A2P3 replacement filters	6 sets of 2 pcs. per box
GVS	SPM007	Integra case	5 pcs. per box
F.	SPM520	Peel off visor x 10	10 sets per

Construction

Paint, moulds.



Car & Ship Repair

Epoxite, paint, solvents



