

DISTRIBUTED BY:

# Sedulitas

PEOPLE | PASSION | PRECISION

info@sedulitas.co.za +27 (0)82 551 4001  
www.sedulitas.co.za



## DOSEman

### Technical Data

---

- Theory of operation
  - HV biased measurement chamber with diffusion membran for air inlet
  - Electrostatic collection of Radon daughters generated by Radon decay within the chamber on the surface of a semiconductor detector
  - Spectroscopic analysis of collected short living Radon daughter products
- Measurement range 0 ... 4 MBq/m<sup>3</sup>
- Response time 12/120 Minutes to 95% of the final value
- Sensitivity 0.18/0.32 Counts/Minute @ 1000 Bq/m<sup>3</sup> (fast/slow mode)
  - 20% statistical error (1σ) @ 200 Bq/m<sup>3</sup> within 8 hours (slow mode)
  - 10% statistical error (1σ) @ 200 Bq/m<sup>3</sup> within 24 hours (slow mode)
  - 16% statistical error (1σ) @ 1000 Bq/m<sup>3</sup> within 2 hours (slow mode)
- Sample interval 1 ... 255 Minutes, adjustable by software
- Non volatile data memory to store 720 data records and sum spectrum
- Internal real time clock
- Internal rechargeable battery for 12 days permanent operation  
2 hours recharge time
- Instrument control by a single push button, Optical and audible alert
- Displaying of concentration, exposure and dose (LCD, 3 lines x 12 characters)
- Dimensions 115 x 57 x 32 mm, weight 250 g
- Available with SI- or US- units
- Infrared interface , spezial IR – USB adapter is required
- Data transfer, set-up and instrument control by Radon Vision software

---

This specification sheet is for information purposes only and is subject to change without notice. SARAD GmbH makes no warranties, expressed or implied, in this product summary. © SARAD GmbH. All rights reserved.

---

